



CLASSIC EXTERIOR OIL

weathering with character



Natural House Exterior Oil contains plant oils and gum rosin impregnated with refined waxes and earthen oxides.

A semi-transparent exterior timber finish formulated for softwoods and hardwoods.

For use on weatherboards, decks, pergolas, lattice, trellis, railings and outdoor furniture. Ideal for timber joinery under eaves or verandahs. Protects against checking, cracking and warping.

Plant chemistry finishes will reduce but not prevent mould. They will protect the integrity of the timber while allowing it to weather in its appearance, blending naturally with your environment.

Available in 14 colours, the deeper the colour the better the UV resistance from silvering.

Feeds timber the protection it had as a tree.

Completed sq/mtr cost \$6.00
Product samples available

Use: For preserving, Apply oil at any stage staining/finishing, after noting heavy exterior timber cladding, weather/sun aspects, decks, joinery, rafters, Please note: Cosmetic fencing, lattice, pergolas changes due to wind outdoor furniture etc. blown mould spores and environmental pollution

Preparation: Ensure can be treated with timber is clean, dry and Natural House 'Oxygen free of sawdust, nails or Cleaner'. metal filings.

If accessible, apply one coat to rear side and end grain of timber cladding. This will help promote total protection.

Application: Stir well prior and during application. Apply by brush, roller or spray application.

Apply two even coats 12 - 24 hrs apart.

Remove any excess oil remaining on the surface within a timeframe of 1 hour.

Easiest method to remove any excess oil over a large area is with an old towel on the end of a broom.

Coverage:

Hardwoods 10-12 sqm/L

Softwoods 5-6 sqm/L

Cedar 4 sqm/L

Maintenance: Apply a further third coat, 12-18 months after initial application. Thereafter the average re-coat period is 3-5years on north facing (high UV exposure) surfaces and 5-7 years on south facing (less exposed surfaces).

Cleanup:

Clean brushes/rollers in white spirit, followed by warm soapy water.

Safety Instructions:

Do not pour oil residue into the sewer. Let the remnants dry out and dispose of with your domestic rubbish collection.

Do not crumple soaked rags (otherwise spontaneous combustion may occur).

Composition: Tung Oil, tree resin, carnauba wax, eucalyptus oil, pure white spirit, zinc, manganese, zirconium lead free drier, earthen micro pigments.