



## CLASSIC RESIN OIL AND WAX glowing and tactile



Designed a two coat finish for joinery, fine furniture and instruments.

A velvet finish, oil wax impregnation with high resilience and ease of application Resin Oil and Wax penetrates deeply into the grain, becoming highly water repellent.

The blend of tree resins and plant oils ensures a robust finish while the canauba wax emulsion gives a silken lustre to the surface.

Particularly suited to interior joinery and furniture. Resin Oil and Wax provides a perfect, natural finish. A great pleasure to apply and wonderfully tactile to the touch.

Well suited to fine woodwork finishing.

**Completed sq/mtr cost \$6.00**  
**Product samples available**

**Use:** To enhance and free cloth or floor protect interior wooden surfaces, especially musical instruments and fine wood work; into 5L warm water and designed as a two coat detergent) as your ester, silicate clay, treatment. Also suitable cleaning agent when isoparaffin thinner, cobalt for low to medium traffic damp mopping. This will zirconium dryer (lead floors. Easy care and continue to feed the free). repair. surface and properly maintained, you will

**Surface Preparation:** have a surface for life. The surface must be 'Microwax' can be used absorbent, even, dry, undiluted at any time to clean, free of grease add a patina and to and chemically neutral. increase water Fine sand to a minimum resistance, of 120/150 grade paper (recommended for and dust off thoroughly. kitchen areas).

**Application:** Priming **Cleaning of** the surface is not **implements:** required. Stir well, Immediately after use apply with a good clean equipment with quality bristle brush or citrus thinner or a mohair roller. natural turpentine Temperature must be at followed by detergent least 8 deg C. Do NOT and water. (for best wipe off excess. Buff out results use a plant after drying, best within based detergent) the time frame of 10 minutes to 1 hour. The

**Safety Instructions:** longer you wait before Keep out of reach of buffing the less the children. Do not pour patina. oil residue into the In most situations a sewer. Let the remnants second coat will be dry out and dispose of required. The surface with your domestic can optionally be buffed rubbish collection, between coats. 'flammable product'. Treat floors after 5 days Do not crumple soaked with undiluted 'Classic rags (otherwise Microwax'. Apply spontaneous combustion sparingly and buff may occur). afterwards with a lint