



CLASSIC HARD VARNISH

resilient high gloss



A marine grade interior, exterior, high gloss, resin based varnish developed for timber floors and joinery. Can be brushed to a superb lacquer finish. Classic Hard Varnish is ideal for timber floors and joinery where a traditional high gloss finish is desired. Being a marine grade product it is extremely durable, making the varnish very suited to wet environments like bathrooms and kitchens.

Many contemporary and traditional homes complement a Gloss Varnish, careful brushwork and fine sanding between coats can build a wonderful reflective finish.

As a healthy alternative to polyurethane on your floors Classic Hard Varnish is an easily applied three coat system by brush or roller.

Completed sq/mtr cost \$10.00
Product samples available

Use: For interior and exterior timber surfaces, floors T&G, parquet and

for protection of all wet areas.

Preparation: The surface must be dry, clean and free of grease. Special care should be taken to remove any dust from the pores of the timber.

humidity the surface will be tack dry after 3 - 5 hours.

Wait 12 - 24 hours for each coat to be dry before lightly sanding

(240 grit sandpaper) applying a further coat. Floors can normally be walked on after 24 hours, final hardness will be achieved after 28 days.

New Surfaces: Sand the surface to a fine finish, 150 grade. Prime with a natural solvent based oil (available from the Natural House Company) or with Gloss Varnish thinned 20% with Citrus Thinner before applying 2-3 coats of undiluted Varnish.

Renovated Surfaces: Old, well preserved coatings should be given a light sand. Apply 1 to 2 coats of Gloss Varnish. Old damaged and weathered coatings should be completely removed and then treated as a new surface.

Application: Coverage approx 17 sqm/L depending on absorbency. The temperature should be at least 8 deg C. Stir well and apply with brush or fine nap mohair/enamel roller to give a thin even coat. At 20 deg C and normal

Cleanup: Clean brushes/rollers in white spirit, followed by warm soapy water.

Safety Instructions: Keep out of reach of children. Do not pour oil residue into the sewer. Let the remnants dry out and dispose of with your domestic rubbish collection, 'flammable product'.

Composition: Tung oil, Linseed stand oil, Dammar, modified Colophony, Citrus turpene, Balm Turpentine, Silicic acid, Lead and Barium free drying agents.